


Specifications:

- Sealed ball bearings
- Loads up to 80 lbs.* (36 Kg)
- Belt speeds up to 264 ft/min. (81 M/min)
- Belt widths: 1.75" (44) to 24" (610)
- Conveyor lengths: 18" (456) to 18' (5,486)
- Cleats available from .24" (6) to 2.36" (60) high.
- 1.25" (32) diameter drive and idler pulleys turn approximately 4.2" (107) of belt per revolution
- 12mm diameter integral drive shaft
- V-grooved 14 gauge stainless steel bedplate
- Metric fasteners
-  models available

Features/Benefits:

- Quick 5 minute belt change.
- Rack pinion belt tensioning for fast, accurate single point belt tensioning.
- Aluminum die cast head plates eliminate painted surfaces.
- V-groove bedplate with guided belt provides positive belt tracking, even under demanding side load applications.
- Non V-guided belts use our patented belt tracking cams, offering you the widest belt selection possible.
- Strong, box-like construction resists damaging frame twist.
- 50% more belt take-up extends conveyor belt life.
- Stand mounting brackets are easily re-positioned along the T-slot.
- Special length conveyors to .12" (4) increments at standard price and delivery.
- Motion Sensor Ready.

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.