



### Specifications:

- Sealed ball bearings (not included on Nose Bar)
- Loads up to 120 lbs.\* (54 Kg)
- Belt speeds up to 264 ft/min (81 M/min)
- Belt widths: 1.75" (44) to 24" (610)
- Conveyor lengths: 24" (610) to 24' (5,486)
- 1.25" (32) diameter drive and idler pulleys turn approximately 4.2" (107) of belt per revolution
- V-grooved 14 gauge stainless steel bedplate
- 12 mm diameter integral drive shaft
- Metric fasteners
- CE models available

### Features/Benefits:

- Center Drive module frees up both ends of conveyor for operator and machine interface
- The Center Drive Module can be easily repositioned along the length of the conveyor
- Maintenance free gas spring belt tensioner maintains uniform belt tension
- Aluminum die cast head plates eliminate painted end surfaces
- V-groove bedplate with guided belt provides positive belt tracking, even under demanding side load applications
- Non V-guided belts use our patented belt tracking cams, offering you the widest belt selection possible
- Strong, box-like construction resists damaging frame twist
- 2" (51) of belt take up extends conveyor belt life
- Stand mounting brackets are easily re-positioned along the t-slot
- Special length conveyors to .12" (4) increments at standard price and delivery
- Motion sensor switch ready

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.